

LED Direct Wire 4ft. Tube

SPECIFICATIONS

Ideal For

T8 & T12 Fluorescent Fixtures

Cool White
4000K

Features

- Shatter Proof Acrylic Lens
- UL 1598C Compliant
- Non-Dimmable
- Indoor Use Only
- UL Listed
- FCC Compliant
- RoHS Compliant
- 100% Mercury Free
- 5 Year Warranty
- Cool White
- DLC Qualified Integrated LED Tube

Benefits

- No Lamp Holder Replacement or Re-Wiring of Lamp Holders Required
- Easy Five (6) Step Installation With Wire Nut Quick Connects (Provided)
- No Ballast Replacement Required
- Eliminates Flicker From T12 Fluorescent Lamps
- Eliminates Humming & Buzzing Associated with T12 Fluorescent Lamps
- Instant Full Brightness (Including Sub-Zero Temperatures)
- 50,000 Hour Rated Life



Specifications

Item Number	Input Power (Watts)	Input Line Voltage	CCT
T4819/840/LEDG2/MP	18.5	100-277	4000K
Base Type	Lumens	Lumen Efficiency (LPW)	Minimum Starting Temperature
G13	2090	112	-13°F
MOL	Diameter	Life Hours	
48"	1"	50,000	

LM-79 and LM-80 data available upon request.