

LED HYBRID (TYPE A & B)

SPECIFICATIONS

Ideal For

T8 Fluorescent Lamps

Daylight Deluxe
6500K

Features

- T8 Plug & Play Replaces 59w T8 Lamps
- T8 & T12 Replaces 59w T8 or 75w T12 Lamps (single pin only - not for use as HO replacement)
- Uses Two 4ft LED Lamps with Quick Connect to Create an 8ft Lamp
- Shatter Resistant Coating
- Non-Dimmable
- Indoor / Suitable for Damp Locations
- ETL Listed
- FCC Compliant
- 100% Glass and Mercury Free
- 5 Year Warranty
- Daylight Deluxe

Benefits

- All-In-One Plug & Play and Ballast Bypass
- Instant Full Brightness (including sub-zero temperatures)
- Direct Replacement for T8 & T12 Fluorescent Lamps (bypass only)
- No Flickering or Strobging
- Operates with Existing T8 Electronic Instant Start Ballast
- 50,000 Hour Rated Life
- No Socket Replacement Necessary (when ballast is bypassed)

Specifications

Item Number	Input Power (Watts)	Input Line Voltage	Base Type
T96/865/AB/LED	42	120-277V	Single Pin Base Fa8
Lumens	Lumen Efficiency (LPW)	CCT	MOL
5200	123	6500K	96"
Diameter	Life Hours	Minimum Starting Temperature	
1"	50,000	-13°F	

LM-79 and LM-80 data available upon request.