

### 353107-TAPE16/RGBW/EU

Useful luminous flux(Lm)*	130
Correlated colour temperature (K) *	3500
The beam angel or range of beam angles(0)*	N/A
Electrical interface details*	220-240V 50/60Hz
The L70B50 life time expressed in hours	17,520H
The on-mode power (Pon) expressed in W	2.5
Lamp Dimensions(mm)	500*10*2.7
The standby power (Psb) expressed in W	0.47
The networked standby power (Pnet) for CLS expressed in W	0.49
The Colour rendering index 80	83.9
Survival factor (Max value =1)	1
Lumen maintenance factor (Max value =1)	96.19%
Displacement factor (Max value =1)	0.4348
Colour consistency in McAdam ellipses (Max value =9)	5.5
Flicker metric (Max value =9.9)	0.003
Stroboscopic effect metric (Max value =9.9)	0.001
Spectral power distribution in the range 250 nm to 800 nm, at full-load (File to be uploaded)	Spectral Power Distribution-353107-TAPE16/RGBW/AG/EU
If the light source is designed for optimum use in nonstandard conditions (such as ambient temperature $T_a \neq 25$ OC or specific thermal management is necessary)	N/A
A warning if the light source cannot be dimmed or can be dimmed only with specific dimmers or with specific wired or wireless dimming methods	
Mercury content x,x mg (if applition) 0,0	0
Energy Efficacy Class	G